

Indexable milling – group 1 (FMA07/11/12, FMD02, FMP12, EMP09/13)

	Material group	Composition / structure / heat treatment	Brinell hardness HB	Machining group	Starting values for cutting speed v_c [m/min]								
					HC (CVD)								
					YBC302		YBC401		YBD152		YBD252		
					a_e / D		a_e / D		a_e / D		a_e / D		
	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5					
A Turning	Unalloyed steel	approx. 0,15 % C	annealed	125	1	260	300	225	260				
		approx. 0,45 % C	annealed	190	2	225	255	195	225				
		approx. 0,45 % C	tempered	250	3	210	240	180	210				
		approx. 0,75 % C	annealed	270	4	185	210	160	185				
		approx. 0,75 % C	tempered	300	5	170	195	150	170				
B Milling	Low-alloyed steel		annealed	180	6	225	255	195	225				
			tempered	275	7	185	210	160	185				
			tempered	300	8	170	195	150	170				
			tempered	350	9	145	165	125	145				
	High-alloyed steel and high-alloyed tool steel	annealed	200	10	130	150	115	130					
	hardened and tempered	325	11	95	105	80	95						
M	Stainless steel	ferritic/martensitic	annealed	200	12								
			martensitic	tempered	240	13							
			austenitic	quench hardened	180	14							
			austenitic-ferritic		230	15							
K	Grey cast iron	perlitic/ferritic		180	16					370	430	320	370
			perlitic (martensitic)		260	17				220	255	190	220
	Cast iron with spheroidal graphite	ferritic		160	18					255	295	220	255
			perlitic		250	19				170	200	145	170
	Malleable cast iron	ferritic		130	20					305	355	265	305
		perlitic		230	21				205	240	175	205	
N Drilling	Aluminium wrought alloys	cannot be hardened		60	22								
		hardenable	hardened	100	23								
	Cast aluminium alloys	$\leq 12\% \text{ Si}$, cannot be hardened		75	24								
		$\leq 12\% \text{ Si}$, hardenable	hardened	90	25								
		$> 12\% \text{ Si}$, cannot be hardened		130	26								
	Copper and copper alloys (bronze/brass)	machining steel, PB > 1%		110	27								
CuZn, CuSnZn		90	28										
CuSn, Pb-free copper, electrolytic copper		100	29										
S	Heat-resistant alloys	Fe-based alloys	annealed	200	30								
			hardened	280	31								
		Ni or Co bass	annealed	250	32								
			hardened	350	33								
		cast	320	34									
Titanium alloys	pure titanium		R_m 400	35									
	α and β alloys	hardened		R_m 1050	36								
H Technical Information	Hardened steel		hardened and tempered	55 HRC	37								
			hardened and tempered	60 HRC	38								
	Hard cast iron		cast	400	39								
	Hardened cast iron		hardened and tempered	55 HRC	40								
X	Non-metallic materials	Thermoplasts			41								
		Thermosetting plastics			42								
		Plastic, glass-fibre reinforced GFRP			43								
		Plastic, carbon fibre reinforced CFRP			44								
		Graphite			45								
		Wood			46								

Note: The given cutting values are guide values, which were determined under ideal conditions.
 The values have to be adapted in individual cases.
 Feed rate recommendations on page B254.
 For examples of material for cutting tool groups view page D11.

A
Turning

B
Milling

C
Drilling

D
Technical Information

E
Index

A

Turning

B

Milling

C

Drilling

D

Technical Information

E

Index

Starting values for cutting speed v_c [m/min]															
HC (CVD)		HC (PVD)								HW					
YBM253		YBG102		YB9320		YBG205		YBG252		YBG302		YD101		YD201	
a_e / D		a_e / D		a_e / D		a_e / D		a_e / D		a_e / D		a_e / D		a_e / D	
1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5
260	300	270	315	245	285	235	275	230	265	225	260				
225	255	230	270	210	245	200	235	200	230	195	225				
210	240	220	255	200	230	190	220	185	215	180	210				
185	210	190	225	175	200	165	195	165	190	160	185				
170	195	180	205	160	190	155	180	150	175	150	170				
225	255	230	270	210	245	200	235	200	230	195	225				
185	210	190	225	175	200	165	195	165	190	160	185				
170	195	180	205	160	190	155	180	150	175	150	170				
145	165	150	175	135	160	130	155	130	150	125	145				
130	150	135	160	125	145	120	140	115	135	115	130				
95	105	95	115	90	100	85	100	85	95	80	95				
130	150	135	160	125	145	120	140	115	135	115	130				
110	130	115	135	105	120	100	120	100	115	95	110				
140	160	145	170	130	155	125	150	125	145	120	140				
110	130	115	135	105	120	100	120	100	115	95	110				
		300	345	270	315	260	300	255	295	250	290				
		180	205	160	190	155	180	150	175	150	170				
		205	240	185	215	180	210	175	200	170	195				
		135	160	125	145	120	140	115	135	115	130				
		245	285	225	260	215	250	210	240	205	235				
		165	190	150	175	145	165	140	160	135	160				
												1505	1735	1450	1670
												1225	1420	1180	1370
												540	620	515	600
												435	505	420	485
												220	255	215	250
												170	195	160	190
												210	245	205	235
												385	445	370	430

HC Coated carbide
 HT Uncoated carbide, main component (TiC) o. (TiN), cermet
 HC₁ Coated cermet
 HW Uncoated carbide, main component (WC)

Indexable milling – group 2 (FMA01/02/03/04, FME01/02, FMP01/02, EMP01/02/03/04)

	Material group	Composition / structure / heat treatment		Brinell hardness HB	Machining group	Starting values for cutting speed v_c [m/min]								
						HC (CVD)								
						YBC302		YBC401		YBD152		YBD252		
						a_e / D		a_e / D		a_e / D		a_e / D		
						1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	
A Turning	Unalloyed steel	approx. 0,15 % C	annealed	125	1	245	285	210	245					
		approx. 0,45 % C	annealed	190	2	210	245	180	210					
		approx. 0,45 % C	tempered	250	3	200	230	170	200					
		approx. 0,75 % C	annealed	270	4	175	200	150	175					
		approx. 0,75 % C	tempered	300	5	160	190	140	160					
B Milling	Low-alloyed steel		annealed	180	6	210	245	180	210					
			tempered	275	7	175	200	150	175					
			tempered	300	8	160	190	140	160					
			tempered	350	9	135	160	120	135					
	High-alloyed steel and high-alloyed tool steel	annealed	200	10	125	145	105	125						
		hardened and tempered	325	11	90	100	75	90						
M	Stainless steel	ferritic/martensitic	annealed	200	12									
			martensitic	tempered	240	13								
			austenitic	quench hardened	180	14								
			austenitic-ferritic		230	15								
K	Grey cast iron	perlitic/ferritic		180	16					315	365	270	315	
			perlitic (martensitic)	260	17					185	215	160	190	
	Cast iron with spheroidal graphite	ferritic		160	18					215	250	185	215	
			perlitic	250	19					145	170	125	145	
	Malleable cast iron	ferritic		130	20					260	300	225	260	
		perlitic	230	21					175	205	150	175		
N Drilling	Aluminium wrought alloys	cannot be hardened		60	22									
		hardenable	hardened	100	23									
	Cast aluminium alloys	$\leq 12\% \text{ Si}$, cannot be hardened		75	24									
		$\leq 12\% \text{ Si}$, hardenable	hardened	90	25									
		$> 12\% \text{ Si}$, cannot be hardened		130	26									
	Copper and copper alloys (bronze/brass)	machining steel, PB > 1%		110	27									
CuZn, CuSnZn		90	28											
	CuSn, Pb-free copper, electrolytic copper		100	29										
S	Heat-resistant alloys	Fe-based alloys	annealed	200	30									
				hardened	280	31								
		Ni or Co base	annealed	250	32									
				hardened	350	33								
		cast	320	34										
Titanium alloys	pure titanium		R_m 400	35										
	α and β alloys	hardened	R_m 1050	36										
H Technical Information	Hardened steel		hardened and tempered	55 HRC	37									
			hardened and tempered	60 HRC	38									
	Hard cast iron		cast	400	39									
	Hardened cast iron		hardened and tempered	55 HRC	40									
X	Non-metallic materials	Thermoplasts			41									
		Thermosetting plastics			42									
		Plastic, glass-fibre reinforced GFRP			43									
		Plastic, carbon fibre reinforced CFRP			44									
		Graphite			45									
		Wood			46									

Note: The given cutting values are guide values, which were determined under ideal conditions.
 The values have to be adapted in individual cases.
 Feed rate recommendations on page B254.
 For examples of material for cutting tool groups view page D11.

A
Turning
B
Milling
C
Drilling
D
Technical Information
E
Index

Starting values for cutting speed v_c [m/min]																					
HC (CVD)		HC (PVD)														HW				HT	
YBM253		YBG101		YBG102		YBG152		YB9320		YBG205		YBG252		YBG302		YD101		YD201		YNG151	
a_e / D		a_e / D		a_e / D		a_e / D		a_e / D		a_e / D		a_e / D		a_e / D		a_e / D		a_e / D		a_e / D	
1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5
245	285			255	295	240	280	230	265	220	255	215	250	210	245					270	315
210	245			220	255	205	240	200	230	190	220	185	215	180	210					235	270
200	230			205	240	195	225	185	215	180	205	175	200	170	200					220	255
175	200			180	210	170	200	165	190	155	180	155	175	150	175					195	220
160	190			170	195	160	185	150	175	145	170	140	165	140	160					180	210
210	245			220	255	205	240	200	230	190	220	185	215	180	210					235	270
175	200			180	210	170	200	165	190	155	180	155	175	150	175					195	220
160	190			170	195	160	185	150	175	145	170	140	165	140	160					180	210
135	160			145	165	135	155	130	150	125	145	120	140	120	135					150	180
125	145			130	150	120	140	115	135	110	130	110	125	105	125					140	160
90	100			90	105	85	100	85	95	80	90	80	90	75	90					100	110
125	145			130	150	120	140	115	135	110	130	110	125	105	125					135	160
105	120			110	125	105	120	100	115	95	110	95	105	90	105					115	135
130	155			140	160	130	150	125	145	120	140	115	135	115	130					145	170
105	120			110	125	105	120	100	115	95	110	95	105	90	105					115	135
				285	330	265	305	255	295	245	285	240	280	235	275						
				170	195	160	185	150	175	145	170	140	165	140	160						
				195	225	180	210	175	200	165	195	165	190	160	185						
				130	150	120	140	115	135	110	130	110	125	105	125						
				230	270	220	255	210	240	200	230	195	225	190	225						
				155	180	145	170	140	160	135	155	130	150	130	150						
		1505	1735													1205	1390	1040	1200		
		1225	1420													980	1140	850	980		
		540	620													435	500	375	435		
		435	505													350	405	300	350		
		220	255													180	205	155	180		
		170	195													140	160	120	140		
		210	245													170	200	150	170		
		385	445													310	360	265	310		
				75	85	70	80	65	75	65	75	65	75	60	70						
				50	55	50	55	45	50	45	50	45	50	40	45						
				60	70	55	65	55	65	50	55	50	55	50	55						
				35	40	35	40	30	35	30	35	30	35	30	35						
				45	50	45	50	40	45	40	45	40	45	40	45						
				75	85	70	80	65	75	65	75	65	75	60	70						
				75	85	70	80	65	75	65	75	65	75	60	70						

HC Coated carbide
 HT Uncoated carbide, main component (TiC) o. (TiN), cermet
 HC₁ Coated cermet
 HW Uncoated carbide, main component (WC)

A

Turning

B

Milling

C

Drilling

D

Technical Information

E

Index

Indexable milling – group 2 (FMA01/02/03/04, FME01/02, FMP01/02, EMP01/02/03/04)

	Material group	Composition / structure / heat treatment		Brinell hardness HB	Machining group	Starting values for cutting speed vc [m/min]				
						HC1				
						YNG151C				
						ae / D				
						1/1 3/4	1/5			
A Turning	P Unalloyed steel	approx. 0,15 % C	annealed	125	1	285	335			
		approx. 0,45 % C	annealed	190	2	250	285			
		approx. 0,45 % C	tempered	250	3	235	270			
		approx. 0,75 % C	annealed	270	4	205	235			
		approx. 0,75 % C	tempered	300	5	190	225			
	B Milling	P Low-alloyed steel		annealed	180	6	250	285		
				tempered	275	7	205	235		
				tempered	300	8	190	225		
				tempered	350	9	160	190		
	C Drilling	M Stainless steel	ferritic/martensitic	annealed	200	12	145	170		
martensitic			tempered	240	13	120	145			
K Cast iron with spheroidal graphite		austenitic	quench hardened	180	14	155	180			
		austenitic-ferritic		230	15	120	145			
		N Aluminium wrought alloys	perlitic/ferritic		180	16				
			perlitic (martensitic)		260	17				
		N Cast aluminium alloys	ferritic		160	18				
			perlitic		250	19				
N Copper and copper alloys (bronze/brass)			ferritic		130	20				
			perlitic		230	21				
D Technical Information	S Heat-resistant alloys	cannot be hardened		60	22					
		hardenable	hardened	100	23					
		≤ 12% Si, cannot be hardened		75	24					
		≤ 12% Si, hardenable		90	25					
	S Titanium alloys	> 12% Si, cannot be hardened		130	26					
		machining steel, PB> 1%		110	27					
		CuZn, CuSnZn		90	28					
		CuSn, Pb-free copper, electrolytic copper		100	29					
	E Index	H Hardened steel	Fe-based alloys	annealed	200	30				
				hardened	280	31				
Ni or Co bass			annealed	250	32					
			hardened	350	33					
H Hard cast iron		cast		400	39					
		hardened and tempered		55 HRC	37					
E Index	X Non-metallic materials	hardened and tempered		60 HRC	38					
		hardened and tempered		55 HRC	40					
		pure titanium		R _m 400	35					
		α and β alloys		hardened	R _m 1050	36				
		Thermoplasts				41				
		Thermosetting plastics				42				
Plastic, glass-fibre reinforced GFRP				43						
Plastic, carbon fibre reinforced CFRP				44						
Graphite				45						
Wood				46						

Note: The given cutting values are guide values, which were determined under ideal conditions.
 The values have to be adapted in individual cases.
 Feed rate recommendations on page B254.
 For examples of material for cutting tool groups view page D11.

Indexable milling – group 3 (FMR01/02/03/04)

	Material group	Composition / structure / heat treatment		Brinell hardness HB	Machining group	Starting values for cutting speed v_c [m/min]					
						HC (CVD)					
						YBC302			YBC401		
						a_e / D			a_e / D		
	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20					
P	Unalloyed steel	approx. 0,15 % C	annealed	125	1	260	300	390	225	260	340
		approx. 0,45 % C	annealed	190	2	225	255	335	195	225	295
		approx. 0,45 % C	tempered	250	3	210	240	315	180	210	275
		approx. 0,75 % C	annealed	270	4	185	210	275	160	185	245
		approx. 0,75 % C	tempered	300	5	170	195	255	150	170	225
	Low-alloyed steel		annealed	180	6	225	255	335	195	225	295
			tempered	275	7	185	210	275	160	185	245
			tempered	300	8	170	195	255	150	170	225
		tempered	350	9	145	165	215	125	145	190	
High-alloyed steel and high-alloyed tool steel		annealed	200	10	130	150	195	115	130	170	
		hardened and tempered	325	11	95	105	140	80	95	125	
M	Stainless steel	ferritic/martensitic	annealed	200	12						
		martensitic	tempered	240	13						
		austenitic	quench hardened	180	14						
		austenitic-ferritic		230	15						
K	Grey cast iron	perlitic/ferritic		180	16						
		perlitic (martensitic)		260	17						
	Cast iron with spheroidal graphite	ferritic		160	18						
		perlitic		250	19						
	Malleable cast iron	ferritic		130	20						
		perlitic		230	21						
N	Aluminium wrought alloys	cannot be hardened		60	22						
		hardenable	hardened	100	23						
	Cast aluminium alloys	$\leq 12\% \text{ Si}$, cannot be hardened		75	24						
		$\leq 12\% \text{ Si}$, hardenable	hardened	90	25						
		$> 12\% \text{ Si}$, cannot be hardened		130	26						
	Copper and copper alloys (bronze/brass)	machining steel, PB > 1%		110	27						
		CuZn, CuSnZn		90	28						
CuSn, Pb-free copper, electrolytic copper		100	29								
S	Heat-resistant alloys	Fe-based alloys	annealed	200	30						
			hardened	280	31						
		Ni or Co bass	annealed	250	32						
			hardened	350	33						
		cast	320	34							
Titanium alloys	pure titanium		R_m 400	35							
	α and β alloys	hardened	R_m 1050	36							
H	Hardened steel		hardened and tempered	55 HRC	37						
			hardened and tempered	60 HRC	38						
	Hard cast iron		cast	400	39						
	Hardened cast iron		hardened and tempered	55 HRC	40						
X	Non-metallic materials	Thermoplasts			41						
		Thermosetting plastics			42						
		Plastic, glass-fibre reinforced GFRP			43						
		Plastic, carbon fibre reinforced CFRP			44						
		Graphite			45						
		Wood			46						

Note: The given cutting values are guide values, which were determined under ideal conditions.
 The values have to be adapted in individual cases.
 Feed rate recommendations on page B254.
 For examples of material for cutting tool groups view page D11.

Starting values for cutting speed v_c [m/min]																						
HC (CVD)									HC (PVD)													
YBD152			YBD252			YBM253			YBG102			YBG152			YB9320			YBG205				
a_e / D			a_e / D			a_e / D			a_e / D			a_e / D			a_e / D			a_e / D				
1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20		
								260	300	390	270	315	410	255	295	385	245	285	375	235	275	360
								225	255	335	230	270	355	220	255	335	210	245	320	200	235	310
								210	240	315	220	255	335	205	240	315	200	230	300	190	220	290
								185	210	275	190	225	295	180	210	275	175	200	260	165	195	255
								170	195	255	180	205	270	170	195	255	160	190	250	155	180	235
								225	255	335	230	270	355	220	255	335	210	245	320	200	235	310
								185	210	275	190	225	295	180	210	275	175	200	260	165	195	255
								170	195	255	180	205	270	170	195	255	160	190	250	155	180	235
								145	165	215	150	175	230	145	165	215	135	160	210	130	155	205
								130	150	195	135	160	210	130	150	195	125	145	190	120	140	185
								95	105	140	95	115	150	90	105	140	90	100	130	85	100	130
								130	150	195	135	160	205	130	150	195	125	145	190	120	140	180
								110	130	165	115	135	175	110	125	165	105	120	160	100	120	155
								140	160	210	145	170	220	140	160	205	130	155	200	125	150	195
								110	130	165	115	135	175	110	125	165	105	120	160	100	120	155
	345	400	520	300	345	450					300	345	450	285	330	430	270	315	410	260	300	390
	210	245	320	180	205	270					180	205	270	170	195	255	160	190	250	155	180	235
	240	280	365	205	240	315					205	240	315	195	225	295	185	215	280	180	210	275
	160	185	245	135	160	210					135	160	210	130	150	195	125	145	190	120	140	185
	285	330	430	245	285	375					245	285	375	230	270	355	225	260	340	215	250	325
	190	220	290	165	190	250					165	190	250	155	180	235	150	175	230	145	165	215

HC Coated carbide
 HT Uncoated carbide, main component (TiC) o. (TiN), cermet
 HC₁ Coated cermet
 HW Uncoated carbide, main component (WC)

A
Turning
B
Milling
C
Drilling
D
Technical Information
E
Index



Indexable milling – group 3 (FMR01/02/03/04)

	Material group	Composition / structure / heat treatment		Brinell hardness HB	Machining group	Starting values for cutting speed v_c [m/min]					
						HC (PVD)					
						YBG212			YBG252		
						a_e / D			a_e / D		
	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20					
P	Unalloyed steel	approx. 0,15 % C	annealed	125	1	240	280	365	230	265	345
		approx. 0,45 % C	annealed	190	2	205	240	315	200	230	300
		approx. 0,45 % C	tempered	250	3	195	225	295	185	215	280
		approx. 0,75 % C	annealed	270	4	170	200	260	165	190	250
	approx. 0,75 % C	tempered	300	5	160	185	245	150	175	230	
P	Low-alloyed steel		annealed	180	6	205	240	315	200	230	300
			tempered	275	7	170	200	260	165	190	250
			tempered	300	8	160	185	245	150	175	230
		tempered	350	9	135	155	205	130	150	195	
High-alloyed steel and high-alloyed tool steel		annealed	200	10	120	140	185	115	135	180	
		hardened and tempered	325	11	85	100	130	85	95	125	
M	Stainless steel	ferritic/martensitic	annealed	200	12	120	140	185	115	135	175
		martensitic	tempered	240	13	105	120	155	100	115	145
		austenitic	quench hardened	180	14	130	150	195	125	145	185
		austenitic-ferritic		230	15	105	120	155	100	115	145
K	Grey cast iron	perlitic/ferritic		180	16	265	305	400	255	295	385
		perlitic (martensitic)		260	17	160	185	245	150	175	230
	Cast iron with spheroidal graphite	ferritic		160	18	180	210	275	175	200	260
		perlitic		250	19	120	140	185	115	135	180
Malleable cast iron	ferritic		130	20	220	255	335	210	240	315	
	perlitic		230	21	145	170	225	140	160	210	
N	Aluminium wrought alloys	cannot be hardened		60	22						
		hardenable	hardened	100	23						
	Cast aluminium alloys	$\leq 12\% \text{ Si}$, cannot be hardened		75	24						
		$\leq 12\% \text{ Si}$, hardenable	hardened	90	25						
		$> 12\% \text{ Si}$, cannot be hardened		130	26						
	Copper and copper alloys (bronze/brass)	machining steel, PB > 1%		110	27						
CuZn, CuSnZn		90	28								
CuSn, Pb-free copper, electrolytic copper		100	29								
S	Heat-resistant alloys	Fe-based alloys	annealed	200	30						
			hardened	280	31						
		Ni or Co base	annealed	250	32						
			hardened	350	33						
	cast	320	34								
Titanium alloys	pure titanium	R_m 400	35								
α and β alloys	hardened	R_m 1050	36								
H	Hardened steel		hardened and tempered	55 HRC	37						
			hardened and tempered	60 HRC	38						
	Hard cast iron		cast	400	39						
Hardened cast iron		hardened and tempered	55 HRC	40							
X	Non-metallic materials	Thermoplasts			41						
		Thermosetting plastics			42						
		Plastic, glass-fibre reinforced GFRP			43						
		Plastic, carbon fibre reinforced CFRP			44						
		Graphite			45						
		Wood			46						

Note: The given cutting values are guide values, which were determined under ideal conditions.
 The values have to be adapted in individual cases.
 Feed rate recommendations on page B254.
 For examples of material for cutting tool groups view page D11.

Starting values for cutting speed v_c [m/min]

	HC (PVD)			HW			
	YBG302			YD101		YD201	
	a_e / D			a_e / D		a_e / D	
	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/1 3/4	1/5
	225	260	340				
	195	225	295				
	180	210	275				
	160	185	245				
	150	170	225				
	195	225	295				
	160	185	245				
	150	170	225				
	125	145	190				
	115	130	170				
	80	95	125				
	115	130	170				
	95	110	145				
	120	140	185				
	95	110	145				
	250	290	380				
	150	170	225				
	170	195	255				
	115	130	170				
	205	235	310				
	135	160	210				
				1505	1735	1450	1670
				1225	1420	1180	1370
				540	620	515	600
				435	505	420	485
				220	255	215	250
				170	195	160	190
				210	245	205	235
				385	445	370	430

HC Coated carbide
 HT Uncoated carbide, main component (TiC) o. (TiN), cermet
 HC₁ Coated cermet
 HW Uncoated carbide, main component (WC)

A	Turning
B	Milling
C	Drilling
D	Technical Information
E	Index



Indexable milling – group 4 (BMR01/02/03/04, TMP01, CMZ01, CMA01, CMD01)

	Material group	Composition / structure / heat treatment		Brinell hardness HB	Machining group	Starting values for cutting speed v_c [m/min]					
						HC (CVD)					
						YBC302			YBC401		
						a_e / D			a_e / D		
	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20					
P	Unalloyed steel	approx. 0,15 % C	annealed	125	1	235	275	360	200	230	300
		approx. 0,45 % C	annealed	190	2	200	235	310	170	200	260
		approx. 0,45 % C	tempered	250	3	190	220	290	160	185	245
		approx. 0,75 % C	annealed	270	4	165	195	255	140	165	215
		approx. 0,75 % C	tempered	300	5	155	180	235	130	150	195
	Low-alloyed steel		annealed	180	6	200	235	310	170	200	260
			tempered	275	7	165	195	255	140	165	215
			tempered	300	8	155	180	235	130	150	195
		tempered	350	9	130	155	205	110	130	170	
High-alloyed steel and high-alloyed tool steel		annealed	200	10	120	140	185	100	115	150	
		hardened and tempered	325	11	85	100	130	70	85	115	
M	Stainless steel	ferritic/martensitic	annealed	200	12						
		martensitic	tempered	240	13						
		austenitic	quench hardened	180	14						
		austenitic-ferritic		230	15						
K	Grey cast iron	perlitic/ferritic		180	16						
		perlitic (martensitic)		260	17						
	Cast iron with spheroidal graphite	ferritic		160	18						
		perlitic		250	19						
	Malleable cast iron	ferritic		130	20						
		perlitic		230	21						
N	Aluminium wrought alloys	cannot be hardened		60	22						
		hardenable	hardened	100	23						
	Cast aluminium alloys	$\leq 12\% \text{ Si}$, cannot be hardened		75	24						
		$\leq 12\% \text{ Si}$, hardenable	hardened	90	25						
		$> 12\% \text{ Si}$, cannot be hardened		130	26						
	Copper and copper alloys (bronze/brass)	machining steel, PB > 1%		110	27						
		CuZn, CuSnZn		90	28						
CuSn, Pb-free copper, electrolytic copper		100	29								
S	Heat-resistant alloys	Fe-based alloys	annealed	200	30						
			hardened	280	31						
		Ni or Co base	annealed	250	32						
			hardened	350	33						
		cast	320	34							
Titanium alloys	pure titanium		R_m 400	35							
	α and β alloys	hardened	R_m 1050	36							
H	Hardened steel		hardened and tempered	55 HRC	37						
			hardened and tempered	60 HRC	38						
	Hard cast iron		cast	400	39						
	Hardened cast iron		hardened and tempered	55 HRC	40						
X	Non-metallic materials	Thermoplasts			41						
		Thermosetting plastics			42						
		Plastic, glass-fibre reinforced GFRP			43						
		Plastic, carbon fibre reinforced CFRP			44						
		Graphite			45						
		Wood			46						

Note: The given cutting values are guide values, which were determined under ideal conditions.
 The values have to be adapted in individual cases.
 Feed rate recommendations on page B254.
 For examples of material for cutting tool groups view page D11.

Starting values for cutting speed v_c [m/min]																							
HC (CVD)									HC (PVD)														
YBD152			YBD252			YBM253			YBG102			YBG152			YB9320			YBG205					
a_e / D			a_e / D			a_e / D			a_e / D			a_e / D			a_e / D			a_e / D					
1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20			
						235	275	360	245	285	375	230	265	345	220	255	335	210	245	320			
						200	235	310	210	245	320	200	230	300	190	220	290	180	210	275			
						190	220	290	200	230	300	185	215	280	180	205	270	170	200	260			
						165	195	255	175	200	260	165	190	250	155	180	235	150	175	230			
						155	180	235	160	190	250	150	175	230	145	170	225	140	160	210			
						200	235	310	210	245	320	200	230	300	190	220	290	180	210	275			
						165	195	255	175	200	260	165	190	250	155	180	235	150	175	230			
						155	180	235	160	190	250	150	175	230	145	170	225	140	160	210			
						130	155	205	135	160	210	130	150	195	125	145	190	120	135	180			
						120	140	185	125	145	190	115	135	180	110	130	170	105	125	165			
						85	100	130	90	100	130	85	95	125	80	90	120	75	90	120			
						120	140	180	125	145	190	115	135	175	110	130	170	105	125	160			
						100	120	155	105	120	160	100	115	145	95	110	145	90	105	135			
						125	150	195	130	155	200	125	145	185	120	140	180	115	130	170			
						100	120	155	105	120	160	100	115	145	95	110	145	90	105	135			
						300	345	450	260	300	390				270	315	410	255	295	385	245	285	375
						180	210	275	155	180	235				160	190	250	150	175	230	145	170	225
						210	245	320	180	210	275				185	215	280	175	200	260	165	195	255
						140	165	215	120	140	185				125	145	190	115	135	180	110	130	170
						250	290	380	215	250	325				225	260	340	210	240	315	200	230	300
						170	200	260	145	165	215				150	175	230	140	160	210	135	155	205

HC Coated carbide
HT Uncoated carbide, main component (TiC) o. (TiN), cermet
HC₁ Coated cermet
HW Uncoated carbide, main component (WC)

Indexable milling – group 4 (BMR01/02/03/04, TMP01, CMZ01, CMA01, CMD01)

	Material group	Composition / structure / heat treatment		Brinell hardness HB	Machining group	Starting values for cutting speed v_c [m/min]						
						HC (PVD)						
						YBG212			YBG252			
						a_e / D			a_e / D			
	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20						
P	Unalloyed steel	approx. 0,15 % C	annealed	125	1	215	250	325	205	240	315	
		approx. 0,45 % C	annealed	190	2	185	215	280	175	205	270	
		approx. 0,45 % C	tempered	250	3	175	200	260	165	195	255	
		approx. 0,75 % C	annealed	270	4	155	175	230	145	170	225	
		approx. 0,75 % C	tempered	300	5	140	165	215	135	160	210	
	Low-alloyed steel		annealed	180	6	185	215	280	175	205	270	
			tempered	275	7	155	175	230	145	170	225	
			tempered	300	8	140	165	215	135	160	210	
		tempered	350	9	120	140	185	115	135	180		
High-alloyed steel and high-alloyed tool steel		annealed	200	10	110	125	165	105	120	160		
		hardened and tempered	325	11	80	90	120	75	85	115		
M	Stainless steel	ferritic/martensitic	annealed	200	12	110	125	165	105	120	160	
			martensitic	tempered	240	13	95	105	140	90	105	135
			austenitic	quench hardened	180	14	115	135	175	110	130	170
			austenitic-ferritic		230	15	95	105	140	90	105	135
K	Grey cast iron	perlite/ferritic		180	16	240	280	365	230	265	345	
			perlite (martensitic)		260	17	140	165	215	135	160	210
	Cast iron with spheroidal graphite	ferritic		160	18	165	190	250	155	180	235	
			perlite		250	19	110	125	165	105	120	160
Malleable cast iron	ferritic		130	20	195	225	295	185	220	290		
		perlite		230	21	130	150	195	125	145	190	
N	Aluminium wrought alloys	cannot be hardened		60	22							
		hardenable	hardened	100	23							
	Cast aluminium alloys	$\leq 12\% \text{ Si}$, cannot be hardened		75	24							
		$\leq 12\% \text{ Si}$, hardenable	hardened	90	25							
		$> 12\% \text{ Si}$, cannot be hardened		130	26							
	Copper and copper alloys (bronze/brass)	machining steel, PB > 1%		110	27							
CuZn, CuSnZn		90	28									
CuSn, Pb-free copper, electrolytic copper		100	29									
S	Heat-resistant alloys	Fe-based alloys	annealed	200	30							
			hardened	280	31							
		Ni or Co base	annealed	250	32							
			hardened	350	33							
		cast	320	34								
Titanium alloys	pure titanium		R_m 400	35								
	α and β alloys	hardened		R_m 1050	36							
H	Hardened steel		hardened and tempered	55 HRC	37							
			hardened and tempered	60 HRC	38							
	Hard cast iron		cast	400	39							
	Hardened cast iron		hardened and tempered	55 HRC	40							
X	Non-metallic materials	Thermoplasts			41							
		Thermosetting plastics			42							
		Plastic, glass-fibre reinforced GFRP			43							
		Plastic, carbon fibre reinforced CFRP			44							
		Graphite			45							
		Wood			46							

Note: The given cutting values are guide values, which were determined under ideal conditions.
 The values have to be adapted in individual cases.
 Feed rate recommendations on page B254.
 For examples of material for cutting tool groups view page D11.

Indexable milling – group 5 (SMP01/03/05)

	Material group	Composition / structure / heat treatment		Brinell hardness HB	Machining group	Starting values for cutting speed v_c [m/min]			
						HC (CVD)		HC (PVD)	
						YBC302	YBM253	YBG101	YB9320
		a_e / D	a_e / D	a_e / D	a_e / D				
		1/4	1/4	1/4	1/4				
A Turning	P Unalloyed steel	approx. 0,15 % C	annealed	125	1	165	180	190	175
		approx. 0,45 % C	annealed	190	2	145	155	165	150
		approx. 0,45 % C	tempered	250	3	135	145	155	140
		approx. 0,75 % C	annealed	270	4	120	130	135	125
		approx. 0,75 % C	tempered	300	5	110	120	125	115
B Milling	P Low-alloyed steel		annealed	180	6	145	155	165	150
			tempered	275	7	120	130	135	125
			tempered	300	8	110	120	125	115
			tempered	350	9	95	100	105	100
C Drilling	P High-alloyed steel and high-alloyed tool steel		annealed	200	10	85	90	95	90
			hardened and tempered	325	11	60	65	70	65
Milling	M Stainless steel	ferritic/martensitic	annealed	200	12		90	95	90
			tempered	240	13		80	80	75
		austenitic	quench hardened	180	14		100	105	95
				230	15		80	80	75
K Milling	Grey cast iron	perlitic/ferritic		180	16			215	190
			perlitic (martensitic)	260	17			125	115
	Cast iron with spheroidal graphite	ferritic		160	18			145	135
			perlitic	250	19			95	90
	Malleable cast iron	ferritic		130	20			175	160
			perlitic	230	21			115	105
N Milling	Aluminium wrought alloys	cannot be hardened		60	22				
		hardenable	hardened	100	23				
	Cast aluminium alloys	$\leq 12\% \text{ Si}$, cannot be hardened		75	24				
		$\leq 12\% \text{ Si}$, hardenable	hardened	90	25				
		$> 12\% \text{ Si}$, cannot be hardened		130	26				
	Copper and copper alloys (bronze/brass)	machining steel, PB > 1%		110	27				
CuZn, CuSnZn		90	28						
S Milling	Heat-resistant alloys	Fe-based alloys	annealed	200	30				
			hardened	280	31				
		Ni or Co base	annealed	250	32				
			hardened	350	33				
		cast	320	34					
	Titanium alloys	pure titanium		R_m 400	35				
α and β alloys		hardened	R_m 1050	36					
H Milling	Hardened steel	hardened and tempered		55 HRC	37				
		hardened and tempered		60 HRC	38				
	Hard cast iron	cast		400	39				
X Milling	Non-metallic materials	hardened and tempered		55 HRC	40				
		Thermoplasts			41				
		Thermosetting plastics			42				
		Plastic, glass-fibre reinforced GFRP			43				
		Plastic, carbon fibre reinforced CFRP			44				
	Graphite			45					
	Wood			46					

Note: The given cutting values are guide values, which were determined under ideal conditions.
 The values have to be adapted in individual cases.
 Feed rate recommendations on page B254.
 For examples of material for cutting tool groups view page D11.

A
Turning
B
Milling
C
Drilling
D
Technical Information
E
Index

Starting values for cutting speed v_c [m/min]		
HC (PVD)		
YBG205	YBG302	
a_e / D	a_e / D	
1/4	1/4	
170	160	
145	140	
140	130	
120	115	
115	105	
145	140	
120	115	
115	105	
95	90	
85	80	
60	60	
85	80	
75	70	
95	85	
75	70	
185	175	
115	105	
130	120	
85	80	
155	145	
105	100	

- HC Coated carbide
- HT Uncoated carbide, main component (TiC) o. (TiN), cermet
- HC₁ Coated cermet
- HW Uncoated carbide, main component (WC)

- A
- Turning
- B
- Milling
- C
- Drilling
- D
- Technical Information
- E
- Index

Indexable milling – group 6 (FMD03, FME04, FMP03, HMP01)

	Material group	Composition / structure / heat treatment	Brinell hardness HB	Machining group	Starting values for cutting speed v_c [m/min]									
					HC (CVD)									
					YBC302		YBC401		YBD152		YBD252			
					a_e / D		a_e / D		a_e / D		a_e / D			
					1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5		
A Turning	P Unalloyed steel	approx. 0,15 % C	annealed	125	1	200	230	170	200					
		approx. 0,45 % C	annealed	190	2	170	200	145	170					
		approx. 0,45 % C	tempered	250	3	160	185	140	160					
		approx. 0,75 % C	annealed	270	4	140	165	120	140					
		approx. 0,75 % C	tempered	300	5	130	150	115	130					
	B Milling	Low-alloyed steel		annealed	180	6	170	200	145	170				
				tempered	275	7	140	165	120	140				
				tempered	300	8	130	150	115	130				
			tempered	350	9	110	130	95	110					
High-alloyed steel and high-alloyed tool steel		annealed	200	10	100	115	85	100						
		hardened and tempered	325	11	70	85	60	70						
M	Stainless steel	ferritic/martensitic	annealed	200	12									
			martensitic	tempered	240	13								
			austenitic	quench hardened	180	14								
			austenitic-ferritic		230	15								
K	Grey cast iron	perlitic/ferritic		180	16				255	295	220	255		
			perlitic (martensitic)		260	17				150	175	130	150	
	Cast iron with spheroidal graphite		ferritic		160	18				175	205	150	175	
			perlitic		250	19				115	135	100	115	
Malleable cast iron		ferritic		130	20				210	245	180	210		
		perlitic		230	21				140	165	120	140		
N Drilling	Aluminium wrought alloys	cannot be hardened		60	22									
		hardenable	hardened	100	23									
	Cast aluminium alloys	$\leq 12\% \text{ Si}$, cannot be hardened		75	24									
		$\leq 12\% \text{ Si}$, hardenable	hardened	90	25									
		$> 12\% \text{ Si}$, cannot be hardened		130	26									
	Copper and copper alloys (bronze/brass)	machining steel, PB > 1%		110	27									
CuZn, CuSnZn		90	28											
CuSn, Pb-free copper, electrolytic copper		100	29											
S	Heat-resistant alloys	Fe-based alloys	annealed	200	30									
			hardened	280	31									
		Ni or Co base	annealed	250	32									
			hardened	350	33									
		cast	320	34										
Titanium alloys	pure titanium		R_m 400	35										
	α and β alloys	hardened		R_m 1050	36									
H Technical Information	Hardened steel		hardened and tempered	55 HRC	37									
			hardened and tempered	60 HRC	38									
	Hard cast iron		cast	400	39									
	Hardened cast iron		hardened and tempered	55 HRC	40									
X	Non-metallic materials	Thermoplasts			41									
		Thermosetting plastics			42									
		Plastic, glass-fibre reinforced GFRP			43									
		Plastic, carbon fibre reinforced CFRP			44									
		Graphite			45									
		Wood			46									

Note: The given cutting values are guide values, which were determined under ideal conditions.
 The values have to be adapted in individual cases.
 Feed rate recommendations on page B254.
 For examples of material for cutting tool groups view page D11.

A

Turning

B

Milling

C

Drilling

D

Technical Information

E

Index

Starting values for cutting speed v_c [m/min]																
HC (CVD)				HC (PVD)												
YBM253		YBG102		YBG152		YB9320		YBG205		YBG212		YBG252		YBG302		
a_e / D		a_e / D		a_e / D		a_e / D		a_e / D		a_e / D		a_e / D		a_e / D		
1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	1/1 3/4	1/5	
200	230	205	240	195	225	190	220	185	215	185	215	180	210	175	205	
170	200	175	205	170	195	165	190	160	185	160	185	155	180	150	175	
160	185	165	195	160	180	155	180	150	175	150	175	145	170	140	165	
140	165	145	170	140	160	135	155	130	155	130	155	130	150	125	145	
130	150	135	160	130	150	125	145	125	140	125	140	120	140	115	135	
170	200	175	205	170	195	165	190	160	185	160	185	155	180	150	175	
140	165	145	170	140	160	135	155	130	155	130	155	130	150	125	145	
130	150	135	160	130	150	125	145	125	140	125	140	120	140	115	135	
110	130	115	135	110	125	105	125	105	120	105	120	100	120	100	115	
100	115	105	120	100	115	95	110	95	110	95	110	90	105	90	105	
70	85	75	85	70	80	70	80	65	80	65	80	65	75	65	75	
100	115	105	120	100	115	95	110	95	110	95	110	90	105	90	105	
85	100	90	105	85	95	80	95	80	95	80	95	80	90	75	90	
110	125	110	130	105	120	105	120	100	115	100	115	100	115	95	110	
85	100	90	105	85	95	80	95	80	95	80	95	80	90	75	90	
		230	265	215	250	210	245	205	240	205	240	200	230	195	225	
		135	160	130	150	125	145	125	140	125	140	120	140	115	135	
		155	180	150	170	145	165	140	165	140	165	135	160	135	155	
		105	120	100	115	95	110	95	110	95	110	90	105	90	105	
		185	220	180	205	175	200	170	195	170	195	165	190	160	185	
		125	145	120	135	115	135	115	130	115	130	110	130	105	125	

HC Coated carbide
 HT Uncoated carbide, main component (TIC) o. (TiN), cermet
 HC₁ Coated cermet
 HW Uncoated carbide, main component (WC)

A
Turning
B
Milling
C
Drilling
D
Technical Information
E
Index

Indexable milling – group 7 (XMR01, XMP01)

	Material group	Composition / structure / heat treatment		Brinell hardness HB	Machining group	Starting values for cutting speed v_c [m/min]									
						HC (CVD)									
						YBC302			YBD152						
						a_e / D			a_e / D						
						1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20				
P	Unalloyed steel	approx. 0,15 % C	annealed	125	1	260	300	390							
		approx. 0,45 % C	annealed	190	2	225	255	335							
		approx. 0,45 % C	tempered	250	3	210	240	315							
		approx. 0,75 % C	annealed	270	4	185	210	275							
		approx. 0,75 % C	tempered	300	5	170	195	255							
	Low-alloyed steel		annealed	180	6	225	255	335							
			tempered	275	7	185	210	275							
			tempered	300	8	170	195	255							
		tempered	350	9	145	165	215								
High-alloyed steel and high-alloyed tool steel		annealed	200	10	130	150	195								
		hardened and tempered	325	11	95	105	140								
M	Stainless steel	ferritic/martensitic	annealed	200	12										
		martensitic	tempered	240	13										
		austenitic	quench hardened	180	14										
		austenitic-ferritic		230	15										
K	Grey cast iron	perlitic/ferritic		180	16				335	390	510				
		perlitic (martensitic)		260	17				200	230	300				
	Cast iron with spheroidal graphite	ferritic		160	18				225	260	340				
		perlitic		250	19				150	175	230				
	Malleable cast iron	ferritic		130	20				275	320	420				
		perlitic		230	21				185	215	280				
N	Aluminium wrought alloys	cannot be hardened		60	22										
		hardenable	hardened	100	23										
	Cast aluminium alloys	$\leq 12\% \text{ Si}$, cannot be hardened		75	24										
		$\leq 12\% \text{ Si}$, hardenable	hardened	90	25										
		$> 12\% \text{ Si}$, cannot be hardened		130	26										
	Copper and copper alloys (bronze/brass)	machining steel, PB > 1%		110	27										
		CuZn, CuSnZn		90	28										
		CuSn, Pb-free copper, electrolytic copper		100	29										
S	Heat-resistant alloys	Fe-based alloys	annealed	200	30										
			hardened	280	31										
		Ni or Co base	annealed	250	32										
			hardened	350	33										
		cast	320	34											
Titanium alloys	pure titanium		R_m 400	35											
	α and β alloys	hardened		R_m 1050	36										
H	Hardened steel		hardened and tempered	55 HRC	37										
			hardened and tempered	60 HRC	38										
	Hard cast iron		cast	400	39										
	Hardened cast iron		hardened and tempered	55 HRC	40										
X	Non-metallic materials	Thermoplasts			41										
		Thermosetting plastics			42										
		Plastic, glass-fibre reinforced GFRP			43										
		Plastic, carbon fibre reinforced CFRP			44										
		Graphite			45										
		Wood			46										

Note: The given cutting values are guide values, which were determined under ideal conditions.
 The values have to be adapted in individual cases.
 Feed rate recommendations on page B254.
 For examples of material for cutting tool groups view page D11.

Starting values for cutting speed v_c [m/min]																					
HC (CVD)									HC (PVD)												
YBD252			YBM253			YBG102			YBG152			YB9320			YBG205			YBG212			
a_e / D			a_e / D			a_e / D			a_e / D			a_e / D			a_e / D			a_e / D			
1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	
			260	300	390	270	315	410	255	295	385	245	285	375	235	275	360	240	280	365	
			225	255	335	230	270	355	220	255	335	210	245	320	200	235	310	205	240	315	
			210	240	315	220	255	335	205	240	315	200	230	300	190	220	290	195	225	295	
			185	210	275	190	225	295	180	210	275	175	200	260	165	195	255	170	200	260	
			170	195	255	180	205	270	170	195	255	160	190	250	155	180	235	160	185	245	
			225	255	335	230	270	355	220	255	335	210	245	320	200	235	310	205	240	315	
			185	210	275	190	225	295	180	210	275	175	200	260	165	195	255	170	200	260	
			170	195	255	180	205	270	170	195	255	160	190	250	155	180	235	160	185	245	
			145	165	215	150	175	230	145	165	215	135	160	210	130	155	205	135	155	205	
			130	150	195	135	160	210	130	150	195	125	145	190	120	140	185	120	140	185	
			95	105	140	95	115	150	90	105	140	90	100	130	85	100	130	85	100	130	
			130	150	195	135	160	205	130	150	195	125	145	190	120	140	180	120	140	185	
			110	130	165	115	135	175	110	125	165	105	120	160	100	120	155	105	120	155	
			140	160	210	145	170	220	140	160	205	130	155	200	125	150	195	130	150	195	
			110	130	165	115	135	175	110	125	165	105	120	160	100	120	155	105	120	155	
	290	335	440				300	345	450	285	330	430	270	315	410	260	300	390	265	305	400
	170	195	255				180	205	270	170	195	255	160	190	250	155	180	235	160	185	245
	195	225	295				205	240	315	195	225	295	185	215	280	180	210	275	180	210	275
	130	150	195				135	160	210	130	150	195	125	145	190	120	140	185	120	140	185
	235	270	355				245	285	375	230	270	355	225	260	340	215	250	325	220	255	335
	160	180	235				165	190	250	155	180	235	150	175	230	145	165	215	145	170	225

HC Coated carbide
 HT Uncoated carbide, main component (TiC) o. (TiN), cermet
 HC₁ Coated cermet
 HW Uncoated carbide, main component (WC)

A

Turning

B

Milling

C

Drilling

D

Technical Information

E

Index



Indexable milling – group 7 (XMR01, XMP01)

	Material group	Composition / structure / heat treatment		Brinell hardness HB	Machining group	Starting values for cutting speed v_c [m/min]					
						HC (PVD)					
						YBG252			YBG302		
						a_e / D			a_e / D		
	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20					
P	Unalloyed steel	approx. 0,15 % C	annealed	125	1	230	265	345	225	260	340
		approx. 0,45 % C	annealed	190	2	200	230	300	195	225	295
		approx. 0,45 % C	tempered	250	3	185	215	280	180	210	275
		approx. 0,75 % C	annealed	270	4	165	190	250	160	185	245
		approx. 0,75 % C	tempered	300	5	150	175	230	150	170	225
	Low-alloyed steel		annealed	180	6	200	230	300	195	225	295
			tempered	275	7	165	190	250	160	185	245
			tempered	300	8	150	175	230	150	170	225
		tempered	350	9	130	150	195	125	145	190	
High-alloyed steel and high-alloyed tool steel		annealed	200	10	115	135	180	115	130	170	
		hardened and tempered	325	11	85	95	125	80	95	125	
M	Stainless steel	ferritic/martensitic	annealed	200	12	115	135	175	115	130	170
		martensitic	tempered	240	13	100	115	145	95	110	145
		austenitic	quench hardened	180	14	125	145	185	120	140	185
		austenitic-ferritic		230	15	100	115	145	95	110	145
K	Grey cast iron	perlitic/ferritic		180	16	255	295	385	250	290	380
		perlitic (martensitic)		260	17	150	175	230	150	170	225
	Cast iron with spheroidal graphite	ferritic		160	18	175	200	260	170	195	255
		perlitic		250	19	115	135	180	115	130	170
Malleable cast iron	ferritic		130	20	210	240	315	205	235	310	
	perlitic		230	21	140	160	210	135	160	210	
N	Aluminium wrought alloys	cannot be hardened		60	22						
		hardenable	hardened	100	23						
	Cast aluminium alloys	$\leq 12\% \text{ Si}$, cannot be hardened		75	24						
		$\leq 12\% \text{ Si}$, hardenable	hardened	90	25						
		$> 12\% \text{ Si}$, cannot be hardened		130	26						
	Copper and copper alloys (bronze/brass)	machining steel, PB > 1%		110	27						
CuZn, CuSnZn		90	28								
CuSn, Pb-free copper, electrolytic copper		100	29								
S	Heat-resistant alloys	Fe-based alloys	annealed	200	30						
			hardened	280	31						
		Ni or Co base	annealed	250	32						
			hardened	350	33						
		cast	320	34							
Titanium alloys	pure titanium	R_m 400	35								
	α and β alloys	hardened	R_m 1050	36							
H	Hardened steel		hardened and tempered	55 HRC	37						
			hardened and tempered	60 HRC	38						
	Hard cast iron		cast	400	39						
	Hardened cast iron		hardened and tempered	55 HRC	40						
X	Non-metallic materials	Thermoplasts			41						
		Thermosetting plastics			42						
		Plastic, glass-fibre reinforced GFRP			43						
		Plastic, carbon fibre reinforced CFRP			44						
		Graphite			45						
		Wood			46						

Note: The given cutting values are guide values, which were determined under ideal conditions.
 The values have to be adapted in individual cases.
 Feed rate recommendations on page B254.
 For examples of material for cutting tool groups view page D11.

Recommended feed rate

Indexable milling – group1 (FMA07/11/12, FMD02, EMP09/13)

Material group	Feed rate per cutting edge [mm]																		
	EMP09			EMP09			EMP13			EMP13			FMA07			FMA07			
	LNKT08/12			LNKT16			ANGX11			ANGX15			ONHU06			ONHU08			
	Application																		
	F	M	R	F	M	R	F	M	R	F	M	R	F	M	R	F	M	R	
P Unalloyed steel		0,25	0,50		0,28	0,55		0,23			0,25			0,19	0,23		0,19	0,23	
	Low-alloyed steel		0,23	0,47		0,26	0,51		0,22			0,23			0,17	0,22		0,17	0,22
	High-alloyed steel and high-alloyed tool steel		0,22	0,44		0,24	0,48		0,20			0,22			0,16	0,20		0,16	0,20
M Stainless steel		0,18	0,35		0,19	0,39		0,16			0,18								
K Grey cast iron		0,28	0,55		0,30	0,61		0,26			0,28			0,20	0,26		0,20	0,26	
	Cast iron with spheroidal graphite		0,25	0,50		0,28	0,55		0,23			0,25			0,19	0,23		0,19	0,23
	Malleable cast iron		0,25	0,50		0,28	0,55		0,23			0,25			0,19	0,23		0,19	0,23
N Aluminum wrought alloys								0,20			0,21								
	Aluminum cast alloys								0,20			0,21							
	Copper and copper alloys (bronze/brass)								0,18			0,19							
S Heat-resistant alloys																			
	Titanium alloys																		
H Hardened steel																			
	Hard cast iron																		
	Hardened cast iron																		
X Non-metallic materials																			

Note: The given cutting values are guide values, which were determined under ideal conditions.
The values have to be adapted in individual cases.

Indexable milling – group1 (FMA07/11/12, FMD02, EMP09/13)

Material group	Feed rate per cutting edge [mm]																		
	FMP12																		
	WNHU08																		
	Application																		
	F	M	R																
P Unalloyed steel		0,25																	
	Low-alloyed steel		0,23																
	High-alloyed steel and high-alloyed tool steel		0,22																
M Stainless steel		0,18																	
K Grey cast iron		0,28																	
	Cast iron with spheroidal graphite		0,25																
	Malleable cast iron		0,25																
N Aluminium wrought alloys																			
	Aluminum cast alloys																		
	Copper and copper alloys (bronze/brass)																		
S Heat-resistant alloys																			
	Titanium alloys																		
H Hardened steel																			
	Hard cast iron																		
	Hardened cast iron																		
X Non-metallic materials																			

Note: The given cutting values are guide values, which were determined under ideal conditions.
The values have to be adapted in individual cases.

Feed rate per cutting edge [mm]																							
FMA11			FMA11			FMA11			FMA12			FMA12			FMD02			FMD02			FMP12		
SNEG12			SNEG15			SNEG19			ONHU06			ONHU08			PNEG11			HNEX09			WNHU06		
Application																							
F	M	R	F	M	R	F	M	R	F	M	R	F	M	R	F	M	R	F	M	R	F	M	R
	0,20	0,23		0,22	0,25			0,29	0,19	0,23			0,23		0,15	0,20	0,30					0,23	
	0,19	0,21		0,20	0,24			0,27	0,17	0,22			0,22		0,14	0,19	0,28					0,22	
	0,18	0,20		0,19	0,22			0,26	0,16	0,20			0,20		0,13	0,18	0,26					0,20	
	0,14	0,16		0,15	0,18			0,20					0,16									0,16	
	0,22	0,25		0,24	0,28			0,32	0,20	0,26			0,26		0,17	0,22	0,33	0,17	0,22	0,33		0,26	
	0,20	0,23		0,22	0,25			0,29	0,19	0,23			0,23		0,15	0,20	0,30	0,15	0,20	0,30		0,23	
	0,20	0,23		0,22	0,25			0,29	0,19	0,23			0,23		0,15	0,20	0,30	0,15	0,20	0,30		0,23	

F Finishing
M Medium machining
R Roughing

F Finishing
M Medium machining
R Roughing

A
Turning
B
Milling
C
Drilling
D
Technical Information
E
Index



Recommended feed rate

Indexable milling – group 2 (FMA01/02/03/04, FME01/02, FMP01/02, EMP01/02/03/04)

Material group		Feed rate per cutting edge [mm]																	
		FMA01 FMA02			FMA03			FMA03			FMA04			FMA04			FMA04		
		SEET12			SEKN12			SEKN15			OFKT05			OFKR07			ODHT06		
		Application																	
		F	M	R	F	M	R	F	M	R	F	M	R	F	M	R	F	M	R
P	Unalloyed steel	0,15	0,20	0,25		0,18			0,20		0,20	0,25		0,20	0,25		0,20	0,25	
	Low-alloyed steel	0,14	0,19	0,23		0,17			0,19		0,19	0,23		0,19	0,23		0,19	0,23	
	High-alloyed steel and high-alloyed tool steel	0,13	0,18	0,22		0,16			0,18		0,18	0,22		0,18	0,22		0,18	0,22	
M	Stainless steel	0,11	0,14	0,18		0,13			0,14		0,14	0,18		0,14	0,18		0,14	0,18	
K	Grey cast iron	0,17	0,22	0,28		0,20			0,22		0,22	0,28		0,22	0,28		0,22	0,28	
	Cast iron with spheroidal graphite	0,15	0,20	0,25		0,18			0,20		0,20	0,25		0,20	0,25		0,20	0,25	
	Malleable cast iron	0,15	0,20	0,25		0,18			0,20		0,20	0,25		0,20	0,25		0,20	0,25	
N	Aluminium wrought alloys	0,13	0,17	0,21							0,17	0,21		0,17	0,21		0,17	0,21	
	Aluminum cast alloys	0,13	0,17	0,21							0,17	0,21		0,17	0,21		0,17	0,21	
	Copper and copper alloys (bronze/brass)	0,11	0,15	0,19							0,15	0,19		0,15	0,19		0,15	0,19	
S	Heat-resistant alloys	0,11	0,14	0,18							0,14	0,18		0,14	0,18		0,14	0,18	
	Titanium alloys	0,11	0,14	0,18							0,14	0,18		0,14	0,18		0,14	0,18	
H	Hardened steel																		
	Hard cast iron																		
	Hardened cast iron																		
X	Non-metallic materials																		

Note: The given cutting values are guide values, which were determined under ideal conditions.
The values have to be adapted in individual cases.

Indexable milling – group 3 (FMR01/02/03/04) Face milling

Material group		Feed rate per cutting edge [mm]																	
		FMR01			FMR01			FMR02			FMR02			FMR02			FMR03		
		RCKT10			RC*12			RC*12			RCKT16			RCKT20			RDKW07		
		Application																	
		F	M	R	F	M	R	F	M	R	F	M	R	F	M	R	F	M	R
P	Unalloyed steel		0,20	0,25		0,20	0,25		0,20	0,25		0,23	0,29		0,26	0,33		0,17	
	Low-alloyed steel		0,19	0,23		0,19	0,23		0,19	0,23		0,21	0,27		0,25	0,31		0,16	
	High-alloyed steel and high-alloyed tool steel		0,18	0,22		0,18	0,22		0,18	0,22		0,20	0,25		0,23	0,29		0,15	
M	Stainless steel		0,14	0,18		0,14	0,18		0,14	0,18		0,16	0,20		0,19	0,23		0,12	
K	Grey cast iron		0,22	0,28		0,22	0,28		0,22	0,28		0,25	0,32		0,29	0,36		0,19	
	Cast iron with spheroidal graphite		0,20	0,25		0,20	0,25		0,20	0,25		0,23	0,29		0,26	0,33		0,17	
	Malleable cast iron		0,20	0,25		0,20	0,25		0,20	0,25		0,23	0,29		0,26	0,33		0,17	
N	Aluminium wrought alloys					0,17	0,21		0,17	0,21									
	Aluminum cast alloys					0,17	0,21		0,17	0,21									
	Copper and copper alloys (bronze/brass)					0,15	0,19		0,15	0,19									
S	Heat-resistant alloys																		
	Titanium alloys																		
H	Hardened steel																		
	Hard cast iron																		
	Hardened cast iron																		
X	Non-metallic materials																		

Note: The given cutting values are guide values, which were determined under ideal conditions.
The values have to be adapted in individual cases.

A

Turning

Feed rate per cutting edge [mm]																										
FME02			FME03			FME03			FMP01			FMP02			EMP01 EMP02			EMP01 EMP02			EMP03 EMP04					
SPK*12			SPK*12			SPK*15			TPKN22			SEET12			APKT11			APKT16			APKT11					
Application																										
F	M	R	F	M	R	F	M	R	F	M	R	F	M	R	F	M	R	F	M	R	F	M	R	F	M	R
0,20			0,19			0,20			0,20			0,15	0,20	0,25	0,10	0,15	0,20	0,12	0,17	0,23	0,10	0,20	0,25			
0,19			0,17			0,19			0,19			0,14	0,19	0,23	0,09	0,14	0,19	0,11	0,16	0,21	0,09	0,19	0,23			
0,18			0,16			0,18			0,18			0,13	0,18	0,22	0,09	0,13	0,18	0,10	0,15	0,20	0,09	0,18	0,22			
0,14			0,13			0,14			0,14			0,11	0,14	0,18	0,07	0,11	0,14	0,08	0,12	0,16	0,07	0,14	0,18			
0,22			0,20			0,22			0,22			0,17	0,22	0,28	0,11	0,17	0,22	0,13	0,19	0,25	0,11	0,22	0,28			
0,20			0,19			0,20			0,20			0,15	0,20	0,25	0,10	0,15	0,20	0,12	0,17	0,23	0,10	0,20	0,25			
0,20			0,19			0,20			0,20			0,15	0,20	0,25	0,10	0,15	0,20	0,12	0,17	0,23	0,10	0,20	0,25			
												0,13	0,17	0,21	0,09	0,13	0,17	0,10	0,15	0,20	0,09	0,17	0,21			
												0,13	0,17	0,21	0,09	0,13	0,17	0,10	0,15	0,20	0,09	0,17	0,21			
												0,11	0,15	0,19	0,08	0,11	0,15	0,09	0,13	0,18	0,08	0,15	0,19			

F Finishing
M Medium machining
R Roughing

B

Milling

Feed rate per cutting edge [mm]														
FMR03			FMR03			FMR04			FMR04			FMR04		
RDKW08			RD*10			RD*12			RDKW16			RDKW20		
Application														
F	M	R	F	M	R	F	M	R	F	M	R	F	M	R
0,17			0,20			0,15	0,20	0,25	0,17	0,23	0,29	0,2	0,26	0,33
0,16			0,19			0,14	0,19	0,23	0,16	0,21	0,27	0,19	0,25	0,31
0,15			0,18			0,13	0,18	0,22	0,15	0,20	0,25	0,18	0,23	0,29
0,12			0,14			0,11	0,14	0,18	0,12	0,16	0,20	0,14	0,19	0,23
0,19			0,22			0,17	0,22	0,28	0,19	0,25	0,32	0,22	0,29	0,36
0,17			0,20			0,15	0,20	0,25	0,17	0,23	0,29	0,20	0,26	0,33
0,17			0,20			0,15	0,20	0,25	0,17	0,23	0,29	0,20	0,26	0,33
			0,17			0,13	0,17	0,21						
			0,17			0,13	0,17	0,21						
			0,15			0,11	0,15	0,19						

F Finishing
M Medium machining
R Roughing

C

Drilling

D

Technical Information

E

Index

Recommended feed rate

Indexable milling – group 3 (FMR01/02/03/04) Circular milling

Material group	Feed rate per cutting edge [mm]							
	FMR01	FMR01	FMR02	FMR02	FMR02	FMR03		
	RCKT10	RC*12	RC*12	RCKT16	RCKT20	RDKW07		
	Tool diameter [mm]							
	25-32	40-50	50-100	63-125	160-200	80-125	160-250	15
P Unalloyed steel	0,12	0,16	0,18	0,24	0,32	0,26	0,35	0,07
	0,11	0,14	0,16	0,21	0,28	0,23	0,31	0,06
	0,10	0,13	0,14	0,19	0,26	0,21	0,28	0,06
M Stainless steel	0,07	0,09	0,10	0,14	0,18	0,15	0,20	0,04
K Grey cast iron	0,11	0,14	0,16	0,22	0,29	0,23	0,32	0,06
	0,10	0,13	0,14	0,19	0,26	0,21	0,28	0,06
	0,10	0,13	0,14	0,19	0,26	0,21	0,28	0,06
N Aluminium wrought alloys								
S Heat-resistant alloys								
H Hardened steel								
X Non-metallic materials								

Note: The given cutting values are guide values, which were determined under ideal conditions.
The values have to be adapted in individual cases.

Indexable milling – group 4 (BMR01/02/03/04, TMP01, CMZ01, CMA01, CMD01)

Material group	Feed rate per cutting edge [mm]								
	BMR01	BMR01	BMR01	BMR01	BMR02	BMR02	BMR02	BMR03	BMR03
	ZD*08 / SP*06	ZD*11 / SP*06	ZD*13 / SP*09	ZP*22 / SP*12	ROHX12	ROHX16	ROHX20	-	-
	Tool diameter [mm]								
	20	25	32	40-63	12	16	20	16	20
P Unalloyed steel	0,14	0,21	0,26	0,32	0,10	0,13	0,14	0,13	0,14
	0,10	0,15	0,18	0,22	0,07	0,09	0,10	0,09	0,10
	0,09	0,14	0,17	0,21	0,07	0,08	0,09	0,08	0,09
M Stainless steel	0,08	0,12	0,14	0,18	0,06	0,07	0,08	0,07	0,08
K Grey cast iron	0,18	0,27	0,34	0,42	0,13	0,17	0,18	0,17	0,18
	0,13	0,20	0,25	0,30	0,10	0,12	0,13	0,12	0,13
	0,14	0,21	0,26	0,32	0,10	0,13	0,14	0,13	0,14
N Aluminium wrought alloys									
S Heat-resistant alloys									
H Hardened steel									
X Non-metallic materials									

Note: The given cutting values are guide values, which were determined under ideal conditions.
The values have to be adapted in individual cases.

Feed rate per cutting edge [mm]					
FMR03	FMR03	FMR04	FMR04	FMR04	
RDKW08	RD*10	RD*12	RDKW16	RDKW20	
Tool diameter [mm]					
16-25	32	50-63	80-100	125-160	
0,07	0,12	0,17	0,24	0,30	
0,06	0,11	0,15	0,21	0,26	
0,06	0,10	0,14	0,19	0,24	
0,04	0,07	0,10	0,14	0,17	
0,06	0,11	0,15	0,22	0,27	
0,06	0,10	0,14	0,19	0,24	
0,06	0,10	0,14	0,19	0,24	
	0,10	0,11			
	0,10	0,11			
	0,10	0,11			

Feed rate per cutting edge [mm]												
BMR03	BMR03	BMR03	BMR04	BMR04	BMR04	BMR04	BMR04	BMR04	CMZ01	CMA01	CMD01	
-	-	-	ZOHX12	ZOHX16	ZOHX20	ZOHX25	ZOHX30		SPMT12	SPMT12	SPMT12	
Tool diameter [mm]												
25	30-32	40-50	12	16	20	25	30		12-32	12-32	12-36	
0,21	0,26	0,30	0,10	0,13	0,14	0,16	0,17		0,23	0,23	0,23	
0,15	0,18	0,21	0,07	0,09	0,10	0,11	0,12		0,16	0,16	0,16	
0,14	0,17	0,20	0,07	0,08	0,09	0,10	0,11		0,15	0,15	0,15	
0,12	0,14	0,17	0,06	0,07	0,08	0,09	0,09		0,13	0,13	0,13	
0,27	0,34	0,39	0,13	0,17	0,18	0,21	0,22		0,30	0,30	0,30	
0,20	0,25	0,29	0,10	0,12	0,13	0,15	0,16		0,22	0,22	0,22	
0,21	0,26	0,30	0,10	0,13	0,14	0,16	0,17		0,23	0,23	0,23	

A
Turning
B
Milling
C
Drilling
D
Technical Information
E
Index



Recommended feed rate

Indexable milling – group 5 (SMP01/03/05)

Material group	Feed rate per cutting edge [mm]									
	SMP01	SMP01	SMP01	SMP01	SMP01	SMP03	SMP03	SMP03	SMP03	SMP05
	XSEQ1202	XSEQ1203	XSEQ12T3	XSEQ1204	XSEQ12T4	MPHT06	MPHT08	MPHT12	QC16	
	Tool diameter [mm]									
	63-100	63-100	63-160	63-160	63-160	80-125	125-200	120-200	25-39	
P	Unalloyed steel	0,12	0,12	0,13	0,13	0,14	0,14	0,15	0,16	0,08
	Low-alloyed steel	0,11	0,11	0,12	0,12	0,13	0,13	0,14	0,15	0,08
	High-alloyed steel and high-alloyed tool steel	0,10	0,10	0,11	0,11	0,12	0,12	0,13	0,14	0,07
M	Stainless steel	0,10	0,10	0,11	0,11	0,12	0,12	0,13	0,14	0,07
K	Grey cast iron	0,11	0,11	0,12	0,12	0,13	0,13	0,14	0,15	0,08
	Cast iron with spheroidal graphite	0,11	0,11	0,12	0,12	0,13	0,13	0,14	0,15	0,07
	Malleable cast iron	0,11	0,11	0,12	0,12	0,13	0,13	0,14	0,15	0,07
N	Aluminium wrought alloys									
	Aluminum cast alloys									
	Copper and copper alloys (bronze/brass)									
S	Heat-resistant alloys									
	Titanium alloys									
H	Hardened steel									
	Hard cast iron									
	Hardened cast iron									
X	Non-metallic materials									

Note: The given cutting values are guide values, which were determined under ideal conditions.
The values have to be adapted in individual cases.

Indexable milling – group 6 (FMD03, FME04, FMP03, HMP01)

Material group	Feed rate per cutting edge [mm]																		
	FMD03			FMD03			FME04			FMP03			FMP03			FMP03			
	LNKT20			LNKT25			LNKT15			LNKT12			LNKT15			LNKT20			
	Application																		
	F	M	R	F	M	R	F	M	R	F	M	R	F	M	R	F	M	R	
P	Unalloyed steel			0,50			0,50			0,45			0,45			0,45			0,50
	Low-alloyed steel			0,47			0,47			0,42			0,42			0,42			0,47
	High-alloyed steel and high-alloyed tool steel			0,44			0,44			0,40			0,40			0,40			0,44
M	Stainless steel			0,45			0,45			0,40			0,40			0,40			0,45
K	Grey cast iron			0,55			0,55			0,50			0,50			0,50			0,55
	Cast iron with spheroidal graphite			0,50			0,50			0,45			0,45			0,45			0,50
	Malleable cast iron			0,50			0,50			0,45			0,45			0,45			0,50
N	Aluminium wrought alloys																		
	Aluminum cast alloys																		
	Copper and copper alloys (bronze/brass)																		
S	Heat-resistant alloys																		
	Titanium alloys																		
H	Hardened steel																		
	Hard cast iron																		
	Hardened cast iron																		
X	Non-metallic materials																		

Note: The given cutting values are guide values, which were determined under ideal conditions.
The values have to be adapted in individual cases.

		Feed rate per cutting edge [mm]	
	SMP05		
	QC22		
		Tool diameter [mm]	
	44		
	0,08		
	0,08		
	0,07		
	0,07		
	0,08		
	0,07		
	0,07		

							Feed rate per cutting edge [mm]		
FMP03			HMP01						
LNKT25			SPMT-APKT						
							Application		
F	M	R	F	M	R				
		0,55		0,25					
		0,51		0,23					
		0,48		0,22					
		0,47		0,15					
		0,61		0,28					
		0,55		0,25					
		0,55		0,25					

F Finishing
M Medium machining
R Roughing

A
Turning
B
Milling
C
Drilling
D
Technical Information
E
Index



Recommended feed rate

Indexable milling – group7 (XMR01, XMP01, QCH)

Material group	Feed rate per cutting edge [mm]									
	XMR01 face milling			XMR01 plunge milling			XMR01 circular milling			
	SDMT/WPGT			SDMT/WPGT			SDMT/WPGT			
	Tool diameter [mm]									
	20-25	30-50	63-160	20-25	30-50	63-160	20-25	30-50	63-160	
P	Unalloyed steel	1,00	1,20	2,00	0,20	0,25	0,30	0,80	0,96	1,40
	Low-alloyed steel	0,93	1,12	1,86	0,19	0,23	0,28	0,74	0,89	1,30
	High-alloyed steel and high-alloyed tool steel	0,70	0,84	1,40	0,18	0,22	0,26	0,70	0,84	1,23
M	Stainless steel	0,50	0,60	1,00	0,14	0,18	0,21	0,56	0,67	0,98
K	Grey cast iron	0,90	1,08	1,80	0,22	0,28	0,33	0,88	1,06	1,54
	Cast iron with spheroidal graphite	0,90	1,08	1,80	0,20	0,25	0,30	0,80	0,96	1,40
	Malleable cast iron	1,00	1,20	2,00	0,20	0,25	0,30	0,80	0,96	1,40
N	Aluminium wrought alloys									
	Aluminum cast alloys									
	Copper and copper alloys (bronze/brass)									
S	Heat-resistant alloys									
	Titanium alloys									
H	Hardened steel									
	Hard cast iron									
	Hardened cast iron									
X	Non-metallic materials									

Note: The given cutting values are guide values, which were determined under ideal conditions.
The values have to be adapted in individual cases.

A

Turning

B

Milling

C

Drilling

D

Technical Information

E

Index

Feed rate per cutting edge [mm]								
	XMP01	QCH	QCH	QCH	QCH	QCH	QCH	
	CNE	ZOHX	RD*	APKT	WPGT	SDMT	XPHT	
Tool diameter [mm]								
	80-400	16-32	15-32	16-40	20-42	20-40	16-32	
	0,20	0,20	0,20	0,15	1,00	1,00	0,20	
	0,20	0,19	0,19	0,14	0,93	0,93	0,19	
	0,20	0,18	0,18	0,13	0,70	0,70	0,18	
	0,20	0,14	0,14	0,11	0,50	0,50	0,14	
	0,20	0,22	0,22	0,17	0,90	0,90	0,22	
	0,20	0,20	0,20	0,15	0,90	0,90	0,20	
	0,20	0,20	0,20	0,15	1,00	1,00	0,20	
				0,13				
				0,13				
				0,11				

A
Turning
B
Milling
C
Drilling
D
Technical Information
E
Index